



**MARINE
CARE**

CARECHLOR

Heavy duty, water based, chlorine alkaline tank cleaner

- Effective dye removal
- Suitable on zinc and epoxy coatings.
- Works at low temperature
- Approved by:
> IMO

DESCRIPTION

Carechlor is a high alkaline, chlorine based product for the removal of discoloration stains in cargo tanks caused by soot or red/ and or yellow dyed gasoline cargoes from epoxy and zinc based tank coatings.

ADVANTAGE

- Suitable on epoxy and zinc tank coatings
- Fast acting
- Biodegradable
- Does not contain nonyl phenol ethoxylates or other estrogenic compounds.
- Free from hydrocarbon solvents
- Effective and economical in use

APPLICATIONS

Tank Cleaning

Carechlor is generally used for removing soot stain deposits from zinc and epoxy coated tanks. It is also very effective for bleaching of stains caused by the carriage of dyed gasoline cargoes.

DIRECTIONS FOR USE

Carechlor is used in a 1-3% solution in fresh or seawater. Circulate at ambient temperatures for 2 – 4 hours. One solution usually is sufficient to clean 3-4 tanks. After this cleaning rinse thoroughly with a sufficient amount of fresh water.

DOSAGE

Circulation 1 - 3% solution



MARINE CARE BV
Oude Maasweg 35
Port number 4005
3197 KJ Rotterdam
The Netherlands
T. +31 (0)10 2950342
F. +31 (0)10 2950345
E. supply@marinecare.nl
W. www.marinecare.nl

PROPERTIES

Article number	14616 / 16616
pH (1 % solution)	> 11
Density	1,20 g/cm ³
Flashpoint	None
Physical state	Liquid

APPROVALS

- IMO approved in accordance with MEPC 590 Guidelines

For detailed information on safety and health, please refer to the Material Safety Data Sheet MSDS and/or product label.



MARINE CARE

CARECHLOR

- Effective dye removal
- Suitable on zinc and epoxy coatings
- Approved by:
> IMO



MARINE CARE BV
Oude Maasweg 35
Port number 4005
3197 KJ Rotterdam
The Netherlands
T. +31 (0)10 2950342
F. +31 (0)10 2950345
E. supply@marinecare.nl
W. www.marinecare.nl