



**MARINE
CARE**

CARETREAT OXYGEN CONTROL SB

Quick acting oxygen scavenger for boiler feed-water of low and medium pressure steam systems

DESCRIPTION

Caretreat Oxygen Control SB is a liquid highly concentrated product based on Sulfite. Caretreat Oxygen Control SB reacts quickly with the Dissolved Oxygen in the boiler feed water, to protect as well the feedwater system as the boiler for corrosion.

ADVANTAGE

- Removes oxygen to protect the feedwater system and boiler from pitting and general corrosion
- Environmentally safe, non-toxic product
- Simple and accurate testing
- Effective under all operating conditions

APPLICATIONS

Caretreat Oxygen Control SB can be used in any type low and medium pressure boiler system. Caretreat Oxygen Control SB can be used in the following make-up water:

- evaporated water
- reversed osmosis water
- demineralized water
- softened water

DIRECTIONS FOR USE

Standard water treatment:

Caretreat Oxygen Control SB has to be dosed in to the feedwater line before the suction side of the feedwater pump. We strongly recommend this is done by using a dosing pump. It is also recommended to continually dose to maintain a residual sulfite level of 30 to 50 ppm Sulfite SO_3 . Do mind that the Alkalinity level has to accurately controlled, between P-Alk. of 100 - 200 ppm as CaCO_3

- Excellent oxygen Scavenger
- Prevents pitting
- Low product consumption
- Simple testing



MARINE CARE BV
Oude Maasweg 35
Port number 4005
3197 KJ Rotterdam Botlek
The Netherlands
T. +31 (0)10 2950342
F. +31 (0)10 2950345
E. supply@marinecare.nl
W. www.marinecare.nl

| | | | |
|---------------|------------|-----------------|------------|
| Revision | 2.0 | Document number | PDS-08-169 |
| Date of issue | 16-01-2023 | Page | 1 of 2 |



MARINE CARE

CARETREAT Oxygen Control SB

- Excellent oxygen Scavenger
- Prevents pitting
- Low product consumption
- Simple testing

DIRECTIONS FOR USE (CONTINUED)

The Caretreat Oxygen Control SB consumption is inverted proportional to the feedwater temperature. The feedwater should be as high in temperature as possible. Low temperature feedwater of 50 °C contains 5 x more dissolved oxygen as feedwater of 90 °C.

Control limits

30 - 50 ppm Sulphite SO₃.
100 - 200 ppm Sulphite SO₃ at cold lay-up

Initial dosage

Caretreat Oxygen Control SB is dosed as initial dosage in **cold** feed water at a rate of 0,2 liter per ton boiler contents. In hot feedwater an amount of 0,1 liter per ton boiler contents is sufficient.

Daily dosage

Caretreat Oxygen Scavenger is dosed at a feed water temperature of 50 - 60 °C at a rate of 0,1 liter per ton feedwater.

TEST KIT

Caretreat Oxygen Control SB concentration can be analyzed with the Marine Care Oxygen Control test kit.

DOSING SYSTEMS

Marine Care supplies a complete range of dosing systems, from manual operated systems, to custom built computer operated high tech systems, for every application.

PROPERTIES

| | |
|----------------|------------------------|
| Article number | 14409 |
| pH | 4,2 |
| Density | 1,29 g/cm ³ |
| Flashpoint | Not applicable |
| Physical state | Liquid |

For detailed information on safety and health, please refer to the Material Safety Data Sheet MSDS and/or product label.

| | | | |
|---------------|------------|-----------------|------------|
| Revision | 2.0 | Document number | PDS-08-169 |
| Date of issue | 16-01-2023 | Page | 2 of 2 |

This information is based on data that we believe to be accurate and reliable and is intended to be used by persons having the knowledge and skill to apply this product properly. We assume no responsibility for results or damages incurred from their use by the Buyer. No liability (including liability for negligence) will attach to Marine Care or its servants or agents arising out of or in connection with or in relation to this product information.



MARINE CARE BV
Oude Maasweg 35
Port number 4005
3197 KJ Rotterdam Botlek
The Netherlands
T. +31 (0)10 2950342
F. +31 (0)10 2950345
E. supply@marinecare.nl
W. www.marinecare.nl