

CARETECH DISCHARGE KIT 31/2

For rapid discharge of rinse water from holds to head heights > 30 meter.

11 11

n n

FEATURES:

- Epoxy Cable Sealing Base Unique "Epoxy Cable Sealing Base" to ensure 100% capability to block the water vapor into the motor from outside.
- Impeller: Hydrodynamically well-balanced bronze made closed type impeller for maximum performance to assure vibrationless and durable operation.
- Triplex Seal System: Oil-bathed Double mechanical seal (Ceramic/Carbon) plus separate oil seal ensures a longer pump life.
- Compact and Light-Weight: Designed to be light, so easy to carry and handle.
- Quiet: The dynamic balance adjuster enables the pump to run balanced with less noise in addition to underwater operation.
- Economical: Adopted turbine flow design and two poles motors, if you get high head and capacity, then save one-third energy as compared with other brand pumps.

TECHNICAL DATA:

Voltage:440V/Power:1.5kWPhase:3Discharge dia:50mmMax head:31 mtMax flow:0.43 mSolid passage:6 mmPump weigth:26 kgPump heigth:410mmPump dia:355mmHose and cable weight:14 kgBox dimensions:500 x

1.5kW 3 50mm (2") 31 mtr 0.43 m3/min (25,8 m3/h) 6 mm dia 26 kg 410mm 355mm 14 kg 500 x 500 x 500 mm

440V/60Hz

- Robust design
- Head height up to 31 meter
- Including 50 m discharge hose and 50 m electric cable
- Plug and play

MARINE CARE BV Oude Maasweg 35 Port number 4005 3197 KJ Rotterdam The Netherlands T. +31 (0)10 2950342 F. +31 (0)10 2950345 E. supply@marinecare.nl W. www.marinecare.nl