



**MARINE
CARE**

CARECLEAN ECO-SOLVE

Ecologically friendly, heavy duty cleaner for removal and hydrocarbon free cleaning of heavy mineral hydrocarbon deposits.

- Ecologically friendly and biodegradable
- Hydrocarbon free cleaning
- Emulsifying
- Not classified or marine pollutant
- Approved by:
> IMO

DESCRIPTION

Careclean Eco-Solve is an emulsifying cleaning agent for removal of coaltar, crude benzene, lube oils, Petroleum distillate, pyrolyse gas oil, bitumen & similar substances. Careclean Eco-Solve is used for cleaning of (cargo) tanks and heat exchangers. Due to the synergetic mixture of solvents and detergents the removal of residues by flushing is easier and quicker than generally achieved. This results in quicker gas free conditions.

ADVANTAGE

- Effective cleaner which will not leave hydro carbon residues on cleaned surfaces
- Excellent for heavily contaminated systems
- Economical cleaner which can be used as an emulsion with fresh and sea water
- Improved cleaning properties ensuring easier rinse off and removal of (hydrocarbon) residues
- Quicker gas free conditions than similar cleaners
- Not marine pollutant

APPLICATIONS

Tank Cleaning

After discharging, prewash the tanks with seawater at a temperature of 60°C. Prepare a cleaning solution inside the tank which has to be cleaned, depending on contamination, in a dosage of 0.5 - 2 % Careclean Eco-Solve. Heat the solution to approx. 60°C. Start circulation. Continue circulation for about 2-4 hours at the same temperature. Flush tank with water and drain the tank.



MARINE CARE BV
Oude Maasweg 35
Port number 4005
3197 KJ Rotterdam
The Netherlands
T. +31 (0)10 2950342
F. +31 (0)10 2950345
E. supply@marinecare.nl
W. www.marinecare.nl

Revision	2.0	Document number	PDS-08-130
Date of issue	30-03-2020	Page	1 of 2



MARINE CARE

DIRECTIONS FOR USE (SEE APPLICATIONS)

DOSAGE

Recirculation 0.5 - 2* %

*) For specific applications, dosing can be increased.
Contact your Marine Care representative for custom advise.

PROPERTIES

Flashpoint >62 °C
Physical state Liquid
Density 1 kg/l
pH at 5% in fresh water 7

APPROVALS

- IMO approved in accordance with MEPC 590 Guidelines
- Major coating manufacturers. Deviations in temperature, exposure time and concentration to the above stated can vary per coating type, consult the coating manufacturers user guidelines.

For detailed information on safety and health, please refer to the Material Safety Data Sheet MSDS and/or product label.

CARECLEAN
Eco-SOLVE

- Ecologically friendly and biodegradable
- Hydrocarbon free cleaning
- Emulsifying
- Not classified or marine pollutant
- Approvals:
 - > IMO
 - > Major coating manufacturers

Revision	2.0	Document number	PDS-08-130
Date of issue	30-03-2020	Page	2 of 2

This information is based on data that we believe to be accurate and reliable and is intended to be used by persons having the knowledge and skill to apply this product properly. We assume no responsibility for results or damages incurred from their use by the Buyer. No liability (including liability for negligence) will attach to Marine Care or its servants or agents arising out of or in connection with or in relation to this product information.



MARINE CARE BV
Oude Maasweg 35
Port number 4005
3197 KJ Rotterdam
The Netherlands
T. +31 (0)10 2950342
F. +31 (0)10 2950345
E. supply@marinecare.nl
W. www.marinecare.nl